

MojeDelo – JobAd Import WebAPI Techical API documentation

Version 2.4

March 2019

contact: urska.likar@rettro.si
www.rettro.si

Document Control Information

The original document is stored in the electronic form and it is under version control. More than one material or non-material copy of this document may exist at any given time for the purpose of distribution to the intended audience or as a working tool. All such copies of this document are uncontrolled copies and the reader must regard them as such.

Version	Status		Name	Date	Description of changes
1.0	draft	Author	Damijan Seničar	1.2.2018	First version of document.
		Reviewed by	Urša Likar	2.2.2018	
1.1.	doc	Author	Urša Likar	12.2.2018	Some minor updates in chapter 2.Create jobAd.
		Approved by			
1.2.	doc	Author	Damijan Seničar	20.2.2018	Some minor updates in chapter 2.Create jobAd (updated URL).
		Approved by			
1.3.	doc	Author	Damijan Seničar	5.3.2018	Update in 8.Get Category: API now returns workfield ID (=group ID) and workfield name (= group).
		Approved by			
1.5.	doc	Author	Urša Likar	24.4.2018	Update in 2.Create JobAd: Contact name is not mandatory. Added option to un-publish job ad (DeactivateJobAd).
		Reviewed by	Damijan Seničar	7.5.2018	
1.6.	doc	Author	Urša Likar	5.6.2018	Update in 2. Create JobAd: added field ExternalID. Added code JobAdNotConfirmed. Fix of error message.
		Reviewed by			
1.7.	doc	Author	Urša Likar, Andreas Lah	20.6.2018	Update in 3. Create JobAd: new job ad type added (student job positions). Some formatting changes. Added field limitations for Create JobAd.
		Reviewed by			

1.8	Doc	Author	Urša Likar	26.6.2018	Update in 3.2: Field studentSalary is not mandatory.
		Reviewed by			
1.9	Doc	Author	Andreas Lah	7.8.2018	Typo fix in request URL's in chapter 6 Get JobAd Type and later.
		Reviewed by	Urša Likar		
2.0	Doc	Author	Andreas Lah	7.8.2018	Typo fix in request methods in chapter Get Category and "employmenttype".
		Reviewed by	Urša Likar		
2.1	Doc	Author	Andreas Lah	8.8.2018	Typo fix in response (region fixed to regionID).
		Reviewed by	Urša Likar		
2.2	Doc	Author	Andreas Lah	August 2018	Typo fix in example response Get Category. Typo fix in request parameter "ExternalID".
		Reviewed by	Urša Likar		
2.3	Doc	Author	Urša Likar	September 2018	Update in 3. Create Job Ad (removed limitations to 400 char. for fields <i>Description</i> , <i>Offerings</i> , <i>Expectations</i> , <i>AboutCompany</i>). Update in 2. Authentication (improved explanation about accessToken).
		Reviewed by			
2.4	Doc	Author	Urša Likar	November 2018	Update in 3. Create Job Ad (updated recommended length for <i>name</i>). Removed limitations to 400 char. also for Student JobAds.
		Reviewed by			

1 Contents

1	Contents	4
2	Authentication	5
3	Create JobAd	6
3.1	Create jobAd for regular job position	6
3.2	Create jobAd for student job position	10
4	DeleteJobAd	13
5	DeactivateJobAd	14
6	Get jobad type	15
7	List of job ad types	16
8	Get workfield	18
9	List of workfield Id's	19
10	Get category	20
11	Get region	22
12	List of region Id's	23
13	Get education level	25
14	List of education level Id's	26
15	Get work experience	27
16	List of work experience Id's	28
17	Get work time	30
18	List of work time Id's	31
19	Get employment type ID's	32
20	List of employment type	33
21	Get salary range ID's	34
22	List of salary range	36
23	Get career level ID's	37
24	List of career level	38
25	WebApi Codes	39
26	WebApi Status	40

2 Authentication

Authenticate the user with the system and obtain the auth_token.

Request

Method	URL
POST	v1/Authenticate/

Type	Params	Values
POST	ClientID	string
POST	ClientSecret	string

accessToken

accessToken must be sent with all client requests. The accessToken authorizes the API call. It must be included as the "Authorization" header, together with the token type "Bearer". example:

Authorization: "Bearer +P3nI5pZ5BmeBs/6yZr+...="

Response

Status	Response
200	<pre>{ "status": "OK", "code": null, "message": null, "apiVersion": "1", "requestUrl": "https://mddevelapi.mojedelo.com:443/v1/Authenticate", "data": { "accessToken": "+P3nI5pZ5BmeBs/6yZr+ =", "expiresIn": 30, "tokenType": "Bearer" } }</pre> accessToken (string) - all further API calls must have this key in "Authorization" header, together with its tokenType. The value of Authorization header must be: "Bearer " + response.data.AccessToken
200	<pre>{ "status": "Unauthorized", "code": null, "message": "Invalid Keys", "apiVersion": "1",</pre>

	<pre>"requestUrl": "https://mddevel- api.mojedelo.com:443/v1/Authenticate", "data": null }</pre>
--	--

3 Create JobAd

Create new job ad. The structure of request varies according to selected JobAdType. JobAd types that should be used for regular job positions are:

- 35 Free
- 38 Enostavni
- 39 Osnovni
- 40 Premium
- 41 Executive
- 42 Headhunter

JobAd type that should be used for student job positions is:

- 64 Študentski oglas

Used JobAd type defines set of mandatory fields and job ad's flow and behavior in application www.mojedelo.com. JobAd types for regular job positions have different set of fields and flow in application as JobAd type for student job position.

3.1 Create jobAd for regular job position

Request

Method	URL
POST	v2/JobAd/Create

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request for regular job position

Parameters	Values	Required	Default value	Example
------------	--------	----------	---------------	---------

ExternalID	String (max 50 char)	*		98012
Name	String (recommended 45 char)	*		Delavec v proizvodnji
City	String (max 255 char)	*		Celje
Type	Integer	*		38
isForeign	Boolean	*		False (in case of "True", regionIds should be set to ID 53).
workFieldIds	integer array	*		[1,2,3] (max 3)
jobCategory	integer	*		1
regionIds	integer array	*		[1,2,3]
educationLevelIds	integer array	*		[1,2,3]
workExperienceId	integer	*		1
workTimeId	integer	*		1
salaryRangeId	integer			1
careerLevelId	integer			1
employmentTypeIds	integer array	*		[1,2,3]
hasTrialWork	Boolean			False
trialWorkMonths	integer			0
contactName	String (max 255 char)			Kontaktna Oseba

contactPhone	String			+38641564543
applyEmail	String (max 400 char)	(field is required if "applyExtUrl" is empty)		info@mojedelo.com
applyExtUrl	String (max 400 char)	(field is required if "applyEmail" is empty)		http://www.mojedelo.com
description	String	*		Ste pripravljeni na nove izzive...
offerings	String			
expectations	String			
aboutCompany	String			
shortDescription	String (max 400 char)	*		XYZ d.o.o., vodilno mednarodno podjetje...
dateFrom	Date	*		2017-09-18
dateTo	Date	(if date is not specified or >30 days after dateFrom, default value is dateFrom value + 30 days)		2017-11-05

Status	Request
200	Request must/can have following parameters: - Note: parameters, that are mandatory, are marked in the table above with "*". <pre>{ "ExternalID": "98012", "name": "Delavec v proizvodnji", "type": 38, "city": "Celje", "isForeign": "false", "workFieldIds": [</pre>


```

1,
2,
3
],
"jobCategory": 1,
"regionIds": [
1,
2,
3
],
"educationLevelIds": [
1,
2,
3
],
"workExperienceId": 1,
"workTimeId": 1,
"salaryRangeId": 1,
"careerLevelId": 1,

"employmentTypeIds": [
1,
2,
3
],
"hasTrialWork": "False",
"contactName": "Kontaktna Oseba",
"contactPhone": "+38641564543",
"applyEmail": "info@mojedelo.com", //OR//
"applyExtUrl": "http://www.cataneo.de",
"description": "Ste pripravljeni na nove izzive v karieri? Ste
dober organizator dela in motivator sodelavcev?
Vašo prijavo pričakujemo na delovno mesto vodja
prodajnega centra (m/ž).
Vaše vsakodnevne naloge v podjetju bodo
naslednje:
- skrb in odgovornost za brežhibno delovanje in
obratovanje centra,
- motiviranje, razvoj sodelavcev, prenos znanja
in informacij na sodelavce...",
"offerings": "",
"expectations": "",
"aboutCompany": "",
"shortDescription": "XYZ d.o.o., vodilno mednarodno podjetje na
področju upravljanja s človeškimi viri za
svojega naročnika išče novega
sodelavca/ko.",
"dateFrom": "2017-09-18",
"dateTo": "2017-11-05"
}

```

An example response, if JobAd is successfully created, is:

```
{
  "status": "OK",
  "code": null,
  "message": null,
  "apiVersion": "1",
  "requestUrl":
    "https://mddevelapi.mojedelo.com:443/v2/JobAd/Create",
  "data": {
    "jobAdId": 346430,
    "jobAdName": "Delavec v proizvodnji",
    "dateFrom": "2017-10-18",
    "dateTo": "2017-11-05",
    "previewUrl": "https://mddevel-
www.mojedelo.com/predogled/346430"
  }
}
```

An example response, if JobAd is not created, is:

```
{
  "status": "Conflict",
  "code": null,
  "message": "jobAd already exists!",
  "apiVersion": "1",
  "requestUrl": "http://localhost:43982/v2/JobAd/Create",
  "data": {
    "employerId": 121,
    "jobAdId": 405426,
    "jobAdName": "Delavec v proizvodnji",
    "jobAdDateFrom": "18. 09. 2017",
    "jobAdDateTo": "18. 10. 2017",
    "previewUrl": "https://www.mojedelo.loc/predogled/405426"
  }
}
```

3.2 Create jobAd for student job position

Request

Method	URL
POST	v2/JobAd/Create

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request for student job position

Parameters	Values	Required	Default value	Example
ExternalID	String (max 50 char)	*		98012(max 50 char)
Name	String (recommended 45 char)	*		Delavec v proizvodnji (max 50 char)
City	String (max 255 char)	*		Celje
Type	Integer	*		38
isForeign	Boolean	*		False (in case of "True", regionIds should be set to ID 53).
workFieldIds	integer array	*		[1,2,3] (max 3)
regionIds	integer array	*		[1,2,3]
workTimeId	integer	*		1
studentSalary	decimal			4.73 (if sent, value must be ≥4,73 EUR)
contactName	String (max 255 char)			Kontaktna oseba
contactPhone	String			+38641564543
applyEmail	String (max 400 char)	(field is required if "applyExtUrl" is empty)		info@mojedelo.com
applyExtUrl	String (max 400 char)	(field is required)		http://www.mojedelo.com

		if "applyEmail" is empty)		
description	String	*		Ste pripravljeni na nove izzive...
offerings	String			
expectations	String			
aboutCompany	String			
shortDescription	String (max 400 char)	*		XYZ d.o.o., vodilno mednarodno podjetje...
dateFrom	Date	*		2017-09-18
dateTo	Date	(if date is not specified or >30 days after dateFrom, default value is dateFrom value + 30 days)		2017-11-05

Status	Request
200	Request must/can have following parameters: - Note: parameters, that are mandatory, are marked in the table above with "*". <pre>{ "ExternalID": "432432", "name": "Delavec v proizvodnji", "type": 64, // it has to be 64 for student job ad position "city": "Celje", "isForeign": "false", "workFieldIds": [13], "regionIds": [1, 2, 3], "studentSalary": 4.73, "workTimeId": 1, "contactName": "Kontaktna Oseba",</pre>

	<pre> "contactPhone":"+38641564543", "applyEmail":"info@mojedelo.com", "description":"Ste pripravljeni na nove izzive v karieri? Ste dober organizator dela in motivator sodelavcev? Vašo prijavo pričakujemo na delovno mesto vodja prodajnega centra (m/ž). Vaše vsakodnevne naloge v podjetju bodo naslednje: - skrb in odgovornost za brezhibno delovanje in obratovanje centra, - motiviranje, razvoj sodelavcev, prenos znanja in informacij na sodelavce...", "offerings":"", "expectations":"", "aboutCompany":"", "shortDescription":"XYZ d.o.o., vodilno mednarodno podjetje na področju upravljanja s človeškimi viri za svojega naročnika išče novega sodelavca/ko.", "dateFrom": "2018-06-11", "dateTo": "2018-06-21" } </pre> An example response is: - <pre> { "status": "OK", "code": null, "message": null, "apiVersion": "1", "requestUrl": "http://localhost:43982/v2/JobAd/Create", "data": { "employerId": 121, "jobAdId": 405479, "jobAdName": "Delavec v proizvodnji", "jobAdDateFrom": "11. 06. 2018", "jobAdDateTo": "22. 06. 2018", "previewUrl": "https://www.mojedelo.loc/predogled/405479" } } </pre>

4 DeleteJobAd

This method is used if we need to remove jobad from portal www.mojedelo.com and back-office application before its regular expiration date (dateTo). JobAd status will be changed to IsDeleted.

Request

Method	URL
POST	v2/JobAd/Delete/jobadId

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/JobAd/Delete/346430/", "data": null }</pre>

5 DeactivateJobAd

This method is used if we need to un-publish job ad from portal www.mojedelo.com before its regular expiration date (dateTo). Job ad will be removed from the list of published ads and its status will be changed to Pasive.

Request

Method	URL
POST	v2/JobAd/Deactivate/jobadId

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/JobAd/Deactivate/4", "data": null }</pre>

6 Get jobad type

The response of this endpoint contains specific job ad types, defined in the Integration Hub Platform.

Request

Method	URL
GET	<code>v2/Collections/jobAdType/jobAdTypeId</code>

Type	Params	Values
HEAD	Authorization	<code>string</code>

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/jobadtype/38/", "data": { "id": 38, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/jobadtype/38/" }, "value": { "name": "Enostavni", "groupId": null, "group": null } } }</pre>

7 List of job ad types

The response of this endpoint contains all job ad types, defined in the Integration Hub Platform and allowed to be used by external system.

Request

Method	URL
GET	v2/Collections/jobAdType/

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/jobadtype/", "data": [{ "id": 38, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/jobadtype/38/" }, "value": { "name": "Enostavni", "groupId": null, "group": null } }, { "id": 39, "links": { "self": "https:// mddevelapi.mojedelo.com /v2/Collections/jobadtype/39/" }, "value": { "name": "Osnovni", "groupId": null, "group": null } }, { "id": 40, "links": { "self": "https:// mddevelapi.mojedelo.com /v2/Collections/jobadtype/40/" }, </pre>

```

        "value": {
          "name": "Premium",
          "groupId": null,
          "group": null
        }
      },
      {
        "id": 38,
        "links": {
          "self": "https://mddevelapi.mojedelo.com/v2/Collections/jobadtype/38/"
        },
        "value": {
          "name": "Enostavni",
          "groupId": null,
          "group": null
        }
      }
    ],
  }

```

8 Get workfield

The response of this endpoint contains specific work field defined in the Integration Hub Platform. Each job ad must contain 1 - 3 workfield ID's.

Request

Method	URL
GET	v2/Collections/ workfield / workfieldId

Type	Params	Values
HEAD	Authorization	string

accessToken

The **accessToken** that was given in response to v1/**Authenticate**/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/workfield/11", "data": { { "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/workfield/1/" }, "value": { "name": "Administracija", "groupId": null, "group": null } } } }</pre>

9 List of workfield Id's

The response of this endpoint contains list of work fields defined in the Integration Hub Platform.

Each job ad must contain 1 - 3 workfield ID's.

Request

Method	URL
GET	v2/Collections/workfield

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/workfield", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/workfield/1/" }, "value": { "name": "Administracija", "groupId": null, "group": null } }, { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/workfield/2/" }, "value": { "name": "Bančništvo, finance", "groupId": null, "group": null } }] }</pre>

10 Get category

The response of this endpoint contains specific job ad category defined in the Integration Hub Platform.

Request

Method	URL
POST	v2/Collections/category/

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: - <pre>{ "workfields": [1, 2, 3] }</pre> An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/category/", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/category/1/" }, "value": { "name": "Administracija", "groupId": 1, </pre>

	<pre> "group": "Administracija" }, }, { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/category/2/" }, "value": { "name": "Asistent", "groupId": 1, "group": "Administracija" } }] }</pre>
--	--

11 Get region

The response of this endpoint contains specific region defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ region / regionId

Type	Params	Values
HEAD	Authorization	string

accessToken

The **accessToken** that was given in response to v1/**Authenticate/**.

Request

Status	Request
--------	---------

200

Request must have following parameters: -

An example response is: -

```
{
  "status": "success",
  "code": 200,
  "message": null,
  "apiVersion": 1,
  "requestUrl":
    "https://mddevelapi.mojedelo.com/v2/Collections/region/11",
  "data":
    {
      "id": 11,
      "links": {
        "self": "https://mddevelapi.mojedelo.com/v2/Collections,
region/11/"
      },
      "value": {
        "name": "Obalna",
        "groupId": null,
        "group": null
      }
    }
}
```

12 List of region Id's

The response of this endpoint contains list of region Id's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ region

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/region", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/region/1/" }, "value": { "name": "Zasavska", "groupId": null, "group": null } }, { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/region/2/" }, "value": { "name": "Pomurje", "groupId": null, "group": null } }] }</pre>

13 Get education level

The response of this endpoint contains specific education level defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ educationLevel / educationLevelId

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/**Authenticate**/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/educationLevel/0", "data": { "id": 10, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/educationLevel/10/" }, "value": { "name": "VIII./2 - doktorati znanosti / 3. bolonjska stopnja", "groupId": null, "group": null } } }</pre>

	<pre> } } } </pre>
--	--------------------------------------

14 List of education level Id's

The response of this endpoint contains list of education level Id's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/educationLevel

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre> { "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com /v2/Collections/educationLevel", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections educationLevel/1/" </pre>

```

    },
    "value": {
      "name": "I. - 7 razredov osnovne šole ali manj",
      "groupId": null,
      "group": null
    }
  },
  {
    "id": 2,
    "links": {
      "self": "https://mddevelapi.mojedelo.com/v2/Collections/educationLevel/2/"
    },
    "value": {
      "name": "II. - dokončana osnovna šola",
      "groupId": null,
      "group": null
    }
  }
]
}

```

15 Get work experience

The response of this endpoint contains work experience level defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ workexperience / workexperienceId

Type	Params	Values
HEAD	Authorization	string

accessToken

The **accessToken** that was given in response to v1/**Authenticate**/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/ workexperience/10", "data": { "id": 10, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections workexperience/10/" }, "value": { "name": "2 leti", "groupId": null, "group": null } } }</pre>

16 List of work experience Id's

The response of this endpoint contains list of work experience Id's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/workexperience

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to `v1/Authenticate/`.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com /v1/Collections/ workexperience", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections workexperience/1/" }, "value": { "name": " 0-1 let", "groupId": null, "group": null } }, { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections workexperience/2/" }, "value": { "name": " 1-3 leta", "groupId": null, "group": null } }] }</pre>

17 Get work time

The response of this endpoint contains work time defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ <i>worktime</i> / <i>worktimeId</i>

Type	Params	Values
HEAD	Authorization	<i>string</i>

accessToken

The *accessToken* that was given in response to v1/*Authenticate/*.

Request

Status	Request
200	Request have parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/ worktime/2", "data": { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections worktime/2/" }, "value": { "name": "delni delovni čas", "groupId": null, "group": null } } }</pre>

18 List of work time Id's

The response of this endpoint contains list of work time Id's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/worktime

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com /v2/Collections/worktime", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/worktime/1/" }, "value": { "name": "polni delovni čas",</pre>

	<pre> "groupId": null, "group": null }, }, { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/worktime/2/" }, "value": { "name": "delni delovni čas", "groupId": null, "group": null } }] }</pre>
--	---

19 Get employment type ID's

The response of this endpoint contains specific employment type ID's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ employmenttype / employmenttypeId

Type	Params	Values
HEAD	Authorization	string

accessToken

The **accessToken** that was given in response to v1/**Authenticate**/.

Request

Status	Request
200	Request must have following parameters: -

An example response is: -

```
{
  "status": "success",
  "code": 200,
  "message": null,
  "apiVersion": 1,
  "requestUrl":
  "https://mddevelapi.mojedelo.com/v2/Collections/
  employmenttype/1",
  "data":
  {
    "id": 1,
    "links": {
      "self": "https://mddevelapi.mojedelo.com/v2/Collections
  employmenttype/1/"
    },
    "value": {
      "name": "redno, nedoločen d. č.",
      "groupId": null,
      "group": null
    }
  }
}
```

20 List of employment type

The response of this endpoint contains list of employment types defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ employmenttype

Type	Params	Values
HEAD	Authorization	string

accessToken

The **accessToken** that was given in response to v1/**Authenticate/**.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/employmenttype ", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/ employmenttype/1/" }, "value": { "name": "redno, nedoločen d. č.", "groupId": null, "group": null } }, { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/ employmenttype/2/" }, "value": { "name": "redno, določen d. č.", "groupId": null, "group": null } }] }</pre>

21 Get salary range ID's

The response of this endpoint contains specific salary range ID's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/salaryRange/salaryRangeId

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/ salaryRange/1", "data": { "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections salaryRange/1/" }, "value": { "name": "0 - 400 EUR neto", "groupId": null, "group": null } } }</pre>

22 List of salary range

The response of this endpoint contains list of salary range defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/salaryRange

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre>{ "status": "success", "code": 200, "message": null, "apiVersion": 1, "requestUrl": "https://mddevelapi.mojedelo.com/v2/Collections/salaryRange", "data": [{ "id": 1, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections. salaryRange/1/" }, "value": { "name": " 0 - 400 EUR neto", "groupId": null, "group": null } }], }</pre>

	<pre> { "id": 2, "links": { "self": "https://mddevelapi.mojedelo.com/v2/Collections/salaryRange/2/" }, "value": { "name": "400 - 600 EUR neto", "groupId": null, "group": null } }]</pre>
--	--

23 Get career level ID's

The response of this endpoint contains specific career level ID's defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/ careerlevel / careerlevelId

Type	Params	Values
HEAD	Authorization	string

accessToken

The **accessToken** that was given in response to v1/**Authenticate**/.

Request

Status	Request
200	Request must have following parameters: - An example response is: - <pre> { "status": "success",</pre>

```

{
  "code": 200,
  "message": null,
  "apiVersion": 1,
  "requestUrl":
  "https://mddevelapi.mojedelo.com/v2/Collections/careerlevel/1"
  "data":
  {
    {
      "id": 1,
      "links": {
        "self": "https://mddevelapi.mojedelo.com/v2/Collections,
careerlevel/1/"
      },
      "value": {
        "name": "študent",
        "groupId": null,
        "group": null
      }
    }
  }
}

```

24 List of career level

The response of this endpoint contains list of career level defined in the Integration Hub Platform.

Request

Method	URL
GET	v2/Collections/careerlevel

Type	Params	Values
HEAD	Authorization	string

accessToken

The `accessToken` that was given in response to v1/Authenticate/.

Request

Status	Request
200	Request must have following parameters: -

An example response is: -

```
{
  "status": "success",
  "code": 200,
  "message": null,
  "apiVersion": 1,
  "requestUrl":

  "https://mddevelapi.mojedelo.com/v2/Collections/careerlevel",
  "data": [
    {
      "id": 1,
      "links": {
        "self":
        "https://mddevelapi.mojedelo.com/v2/Collections/careerlevel/1/
      },
      "value": {
        "name": "študent",
        "groupId": null,
        "group": null
      }
    },
    {
      "id": 2,
      "links": {
        "self":
        "https://mddevelapi.mojedelo.com/v2/Collections/careerlevel/2/
      },
      "value": {
        "name": "pripravník",
        "groupId": null,
        "group": null
      }
    }
  ]
}
```

25 WebApi Codes

Code	Description
JobAdNotConfirmed	Job ad can't be deactivated, because is not yet confirmed. Example: <pre>{ "status": "ExpectationFailed", "code": "JobAdNotConfirmed", "message": "Job ad cannot be deactivated!, JobAd is not in confirmed status. Inner exception:" }</pre>

	<code>","apiVersion":"1","requestUrl":"https://mdsandbox-api.mojedelo.com:443/v2/JobAd/Deactivate/375674","data":null}</code>
--	---

26 WebApi Status

Status	Description
Conflict	Job ad with received external ID already exists. Example: <pre>{ "status": "Conflict", "code": null, "message": "jobAd already exists!", "apiVersion": "1", "requestUrl": "http://localhost:43982/v2/JobAd/Create", "data": { "employerId": 121, "jobAdId": 405426, "jobAdName": "Delavec v proizvodnji", "jobAdDateFrom": "18. 09. 2017", "jobAdDateTo": "18. 10. 2017", "previewUrl": "https://www.mojedelo.loc/predogled/405426" } }</pre>